

Rectangular Tube Conversion Factors



Member Size (Inches)	Wall Thickness (Inches)	A/P Value	Metric Designation (millimeters)	M/D Value	Hp/A Value	Square Ft. / Lin. Foot	Square M. / Lin. Meter
36 x 24	1/2	0.49	914 x 610 x 12.7	97.4	80.0	10.00	3.05
30 x 24	1/2	0.49	762 x 610 x 12.7	97.4	80.0	9.00	2.74
	3/8	0.37	x 9.5	73.8	105.5	9.00	2.74
	5/16	0.31	x 7.9	61.4	126.8	9.00	2.74
28 x 24	1/2	0.49	711 x 610 x 12.7	97.4	80.0	8.66	2.64
	3/8	0.37	x 9.5	73.8	105.5	8.66	2.64
	5/16	0.31	x 7.9	61.4	126.8	8.66	2.64
26 x 24	1/2	0.49	660 x 610 x 12.7	97.4	80.0	8.33	2.54
	3/8	0.37	x 9.5	73.2	106.4	8.33	2.54
	5/16	0.31	x 7.9	61.4	126.8	8.33	2.54
24 x 22	1/2	0.49	610 x 559 x 12.7	96.8	80.5	7.66	2.33
	3/8	0.37	x 9.5	73.2	106.4	7.66	2.33
	5/16	0.31	x 7.9	61.4	126.8	7.66	2.33
22 x 20	1/2	0.49	559 x 508 x 12.7	96.2	81.0	7.00	2.13
	3/8	0.37	x 9.5	73.2	106.4	7.00	2.13
	5/16	0.31	x 7.9	61.4	126.8	7.00	2.13
20 x 18	1/2	0.49	508 x 457 x 12.7	96.2	81.0	6.33	1.93
	3/8	0.37	x 9.5	72.6	107.3	6.33	1.93
	5/16	0.31	x 7.9	60.8	128.1	6.33	1.93
20 x 12	1/2	0.48	508 x 305 x 12.7	95	82.0	5.33	1.62
	3/8	0.37	x 9.5	72.6	107.3	5.33	1.62
	5/16	0.31	x 7.9	60.8	128.1	5.33	1.62
20 x 8	1/2	0.48	508 x 203 x 12.7	94.4	82.5	4.66	1.42
	3/8	0.36	x 9.5	72	108.2	4.66	1.42
	5/16	0.31	x 7.9	60.2	129.4	4.66	1.42
20 x 4	1/2	0.48	508 x 102 x 12.7	93.2	83.6	4.00	1.22
	3/8	0.36	x 9.5	71.4	109.1	4.00	1.22
	5/16	0.30	x 7.9	60.2	129.4	4.00	1.22
18 x 12	1/2	0.48	457 x 305 x 12.7	95	82.0	5.00	1.52
	3/8	0.37	x 9.5	72	108.2	5.00	1.52
	5/16	0.31	x 7.9	60.8	128.1	5.00	1.52
18 x 6	1/2	0.48	457 x 152 x 12.7	93.2	83.6	4.00	1.22
	3/8	0.36	x 9.5	71.4	109.1	4.00	1.22
	5/16	0.30	x 7.9	60.2	129.4	4.00	1.22
	1/4	0.24	x 6.4	48.4	160.9	4.00	1.22
16 x 12	1/2	0.48	406 x 305 x 12.7	94.4	82.5	4.66	1.42
	3/8	0.36	x 9.5	72	108.2	4.66	1.42
	5/16	0.31	x 7.9	60.2	129.4	4.66	1.42
16 x 8	1/2	0.48	406 x 203 x 12.7	93.2	83.6	4.00	1.22
	3/8	0.36	x 9.5	71.4	109.1	4.00	1.22
	5/16	0.30	x 7.9	60.2	129.4	4.00	1.22
16 x 4	1/2	0.48	406 x 102 x 12.7	92	84.7	3.33	1.01
	3/8	0.35	x 9.5	67.1	116.1	3.33	1.01
	5/16	0.30	x 7.9	59.6	130.7	3.33	1.01

The A/P ratios herein were obtained utilizing the formula as listed in the UL Design. The square foot factors are theoretical based on the dimensions of the shape.

Rectangular Tube Conversion Factors



Member Size (Inches)	Wall Thickness (Inches)	A/P Value	Metric Designation (millimeters)	M/D Value	Hp/A Value	Square Ft. / Lin. Foot	Square M. / Lin. Meter
14 x 10	5/8	0.59	356 x 254 x 15.9	112.1	69.5	4.00	1.22
	1/2	0.48	x 12.7	93.2	83.6	4.00	1.22
	3/8	0.36	x 9.5	71.4	109.1	4.00	1.22
	5/16	0.30	x 7.9	60.2	129.4	4.00	1.22
14 x 6	1/2	0.48	356 x 152 x 12.7	92	84.7	3.33	1.01
	3/8	0.36	x 9.5	70.8	110.0	3.33	1.01
	5/16	0.30	x 7.9	59.6	130.7	3.33	1.01
	1/4	0.24	x 6.4	48.4	160.9	3.33	1.01
14 x 4	1/2	0.47	356 x 102 x 12.7	91.5	85.1	3.00	0.91
	3/8	0.36	x 9.5	70.2	110.9	3.00	0.91
	5/16	0.30	x 7.9	59	132.0	3.00	0.91
	1/4	0.24	x 6.4	47.8	162.9	3.00	0.91
12 x 8	5/8	0.59	305 x 203 x 15.9	112.7	69.1	3.33	1.01
	1/2	0.48	x 12.7	92	84.7	3.33	1.01
	3/8	0.36	x 9.5	71	109.7	3.33	1.01
	5/16	0.30	x 7.9	59.6	130.7	3.33	1.01
	1/4	0.24	x 6.4	48.4	160.9	3.33	1.01
	3/16	0.18	x 4.8	36.6	212.8	3.33	1.01
12 x 6	5/8	0.58	305 x 152 x 15.9	111	70.2	3.00	0.91
	1/2	0.47	x 12.7	91.5	85.1	3.00	0.91
	3/8	0.36	x 9.5	70.2	110.9	3.00	0.91
	5/16	0.30	x 7.9	59	132.0	3.00	0.91
	1/4	0.24	x 6.4	48.8	159.6	3.00	0.91
	3/16	0.18	x 4.8	36.6	212.8	3.00	0.91
12 x 4	5/8	0.58	305 x 102 x 15.9	109.2	71.3	2.66	0.81
	1/2	0.47	x 12.7	90.3	86.2	2.66	0.81
	3/8	0.36	x 9.5	69.6	111.9	2.66	0.81
	5/16	0.30	x 7.9	59	132.0	2.66	0.81
	1/4	0.24	x 6.4	47.8	162.9	2.66	0.81
	3/16	0.18	x 4.8	36	216.3	2.66	0.81
10 x 8	5/8	0.58	254 x 203 x 15.9	110.2	70.7	3.00	0.91
	1/2	0.47	x 12.7	91.5	85.1	3.00	0.91
	3/8	0.36	x 9.5	70.2	110.9	3.00	0.91
	5/16	0.30	x 7.9	59	132.0	3.00	0.91
	1/4	0.24	x 6.4	47.8	162.9	3.00	0.91
	3/16	0.18	x 4.8	36	216.3	3.00	0.91
10 x 6	5/8	0.58	254 x 152 x 15.9	110.2	70.7	2.66	0.81
	1/2	0.47	x 12.7	90.3	86.2	2.66	0.81
	3/8	0.36	x 9.5	69.6	111.9	2.66	0.81
	5/16	0.30	x 7.9	59	132.0	2.66	0.81
	1/4	0.24	x 6.4	47.8	162.9	2.66	0.81
	3/16	0.18	x 4.8	36	216.3	2.66	0.81
10 x 4	1/2	0.46	254 x 102 x 12.7	88.5	88.0	2.33	0.71
	3/8	0.35	x 9.5	68.4	113.9	2.33	0.71
	5/16	0.30	x 7.9	58.4	133.4	2.33	0.71
	1/4	0.24	x 6.4	47.2	165.0	2.33	0.71
	3/16	0.18	x 4.8	36	216.3	2.33	0.71
8 x 6	1/2	0.46	203 x 152 x 12.7	88.5	88.0	2.33	0.71
	3/8	0.35	x 9.5	68.4	113.9	2.33	0.71
	5/16	0.30	x 7.9	57	136.6	2.33	0.71
	1/4	0.24	x 6.4	47.2	165.0	2.33	0.71
	3/16	0.18	x 4.8	36	216.3	2.33	0.71

The A/P ratios herein were obtained utilizing the formula as listed in the UL Design. The square foot factors are theoretical based on the dimensions of the shape.

Rectangular Tube Conversion Factors



Member Size (Inches)	Wall Thickness (Inches)	A/P Value	Metric Designation (millimeters)	M/D Value	Hp/A Value	Square Ft. / Lin. Foot	Square M. / Lin. Meter
8 x 4	1/2	0.46	203 x 102 x 12.7	86.7	89.8	2.00	0.61
	3/8	0.35	x 9.5	67.9	114.7	2.00	0.61
	5/16	0.30	x 7.9	57.2	136.2	2.00	0.61
	1/4	0.24	x 6.4	46.6	167.1	2.00	0.61
	3/16	0.18	x 4.8	36	216.3	2.00	0.61
7 x 5	1/2	0.46	178 x 127 x 12.7	86.7	89.8	2.00	0.61
	3/8	0.35	x 9.5	67.9	114.7	2.00	0.61
	5/16	0.30	x 7.9	57.2	136.2	2.00	0.61
	1/4	0.24	x 6.4	46.6	167.1	2.00	0.61
	3/16	0.18	x 4.8	36	216.3	2.00	0.61
7 x 4	1/2	0.46	178 x 102 x 12.7	87.4	89.1	1.83	0.56
	3/8	0.35	x 9.5	66.7	116.8	1.83	0.56
	5/16	0.29	x 7.9	56.6	137.6	1.83	0.56
	1/4	0.24	x 6.4	46.6	167.1	1.83	0.56
	3/16	0.18	x 4.8	35.4	220.0	1.83	0.56
6 x 4	1/2	0.46	152 x 102 x 12.7	83.8	92.9	1.66	0.51
	3/8	0.35	x 9.5	66.1	117.8	1.66	0.51
	5/16	0.29	x 7.9	56.1	138.8	1.66	0.51
	1/4	0.24	x 6.4	46	169.3	1.66	0.51
	3/16	0.18	x 4.8	35.4	220.0	1.66	0.51
5 x 4	3/8	0.34	127 x 102 x 9.5	65	119.8	1.5	0.46
	5/16	0.29	x 7.9	55.5	140.3	1.5	0.46
	1/4	0.24	x 6.4	45.4	171.5	1.5	0.46
	3/16	0.18	x 4.8	34.8	223.8	1.5	0.46

The A/P ratios herein were obtained utilizing the formula as listed in the UL Design. The square foot factors are theoretical based on the dimensions of the shape.