

Health Hazard	1
Fire Hazard	0
Reactivity	0
Personal Protection	E

HMIS RATING

MATERIAL SAFETY DATA SHEET (OSHA 29 CFR 1910.1200)



NFPA RATING

Effective Date: December 28, 2009
Supersedes: October 17, 2005

Page 1 of 2

SECTION I - PRODUCT INFORMATION

- MANUFACTURER'S NAME AND ADDRESS:**
ISOLATEK INTERNATIONAL/CAFECO INDUSTRIES
41 Furnace Street
Stanhope, NJ 07874
973-347-1200
- EMERGENCY TELEPHONE NUMBER:**
CHEMTREC 703-527-3887
- CHEMICAL NAME AND SYNONYMS**
Spray-Applied Acoustical Treatment
- CHEMICAL FAMILY:**
Calcium Silicates, Calcium Aluminates, Alumino Silicates
- FORMULA:**
Blend of Portland Cement and Vermiculite Aggregate
- TRADE NAMES AND SYNONYMS:**
SOUND-SHIELD®40

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

INGREDIENT	CAS NUMBER	OSHA PEL	ACGIH TLV-TWA
Powdered Binders & Fillers Nuisance Particulates	N/Ap	Total Dust: 15mg/m ³ Respirable Fraction: 5mg/m ³	10mg/m ³ 3mg/m ³

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

- Boiling Point (°F): N/Ap
- Vapor Pressure (mm Hg): N/Ap
- Vapor Density (Air=1): N/Ap
- Solubility in Water: Negligible
- Specific Gravity (H₂O=1): 2.0
- Melting Point (°F): >1800° F (981 °C)
- Evaporation Rate (Butyl Acetate = 1): N/Ap
- Appearance and Odor: White powder with golden pellets and flakes; no odor.
- Physical State: Solid
- % Volatiles: 0
- pH: 12-12.5

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

- Flash Point (Method used): N/Ap
- Flammable Limits: Noncombustible
- Extinguishing Media: N/Ap
- Special Fire Fighting Procedures: N/Ap
- Unusual Fire and Explosion Hazards: None

SECTION V - REACTIVITY DATA

- Stability (under normal conditions): Stable
Conditions to Avoid: Contact with strong acids.
- Incompatibility (Material to Avoid): Strong acids
- Hazardous Decomposition Products: CO, CO₂
- Hazardous Polymerization: Will not occur
Conditions to Avoid: N/Ap

N/Ap = Not Applicable

SECTION VI - HEALTH HAZARD DATA

Primary Routes of Entry: Inhalation, Skin and Eye Contact, Ingestion.

Acute: Inhalation: Dry mix may cause irritation to upper respiratory system.
Skin: When wet, the mix may dry the skin and cause alkali burns.
Eyes: Dry mix may cause irritation to the eyes.

Chronic: Dust may cause inflammation of the cornea; dermatitis may occur in sensitive individuals. Inhalation over long periods of high contaminants of any dust may overload lung clearance mechanisms and make the lungs more vulnerable to disease.

Carcinogenicity: NTP - No IARC - No OSHA - No

Signs and Symptoms of Exposure: Coughing, drying and cracking of skin, eye irritation.

Medical Conditions Generally Aggravated by Exposure: Skin complaints, respiratory conditions. Any condition, which may be aggravated by mechanical irritants.

Emergency and First Aid Procedures:

Eye Contact: Wash eye out with plenty of clean water, and seek medical attention if irritation persists.
Skin Contact: Remove and wash with warm, clean water. If persistent irritation occurs (e.g. if allergic to cement) seek medical attention.
Inhalation: Breath fresh air. If a large amount has been inhaled, or distress is caused, seek medical attention.
Ingestion: Do not induce vomiting. Seek immediate medical attention.

USE NORMAL PERSONAL HYGIENE AFTER CONTACT TO REMOVE ANY MATERIAL CONTAMINANTS.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

- Steps to be taken in case material is released or spilled:
Sweep up and place in disposal containers. Avoid inhalation of dust.
- Waste Disposal Method: Land Fill - In accordance with local, state, and federal regulations.
- Precautions to be taken in handling and storing:
Avoid inhalation of dust during use. Avoid skin and eye contact. Use normal personal hygiene to remove material contaminants.

SECTION VIII - CONTROL MEASURES

- Respiratory Protection: Wear a NIOSH approved dust mask to prevent exposure above the limits specified under Section II.
- Ventilation: Sufficient to maintain dust levels below the limits specified under Section II.
- Protective Gloves: Wear cloth gloves. Hand creams are recommended to prevent drying of skin.
- Eye Protection: Wear proper eye protection.
- Other Protective Equipment: Wear loose fitting long sleeve shirt and pants.
- Work/Hygienic Practices: Use bag opening procedures which minimize dust release. Use anti-slip surfaces on working platforms. THE MIX IS SLIPPERY WHEN WET!

SECTION IX - PREPARATION INFORMATION

Prepared By: Research Department, U.S.A.
Telephone: (973) 347-1200
Effective Date: December 28, 2009

Supersedes: October 17, 2005

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. **VENDOR SPECIFICALLY DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** In no event shall the vendor be liable for special, indirect or consequential damages.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes all risks in his use of the material.