


Health Hazard	①
Fire Hazard	①
Reactivity	①
Personal Protection	⑤

HMIS RATING

MATERIAL SAFETY DATA SHEET (OSHA 29 CFR 1910.1200)



NFPA RATING

Effective Date: August 20, 2008
Supersedes: All Previous Issued

Page 1 of 2

SECTION I - PRODUCT INFORMATION

1. MANUFACTURER'S NAME AND ADDRESS:
United States Mineral Products Company
dba Isolatek International
41 Furnace Street
Stanhope, NJ 07874
2. EMERGENCY TELEPHONE NUMBER:
973-347-1200
3. CHEMICAL NAME AND SYNONYMS
Mineral Wool
4. CHEMICAL FAMILY:
Vitreous Silicate Fibers
5. FORMULA:
N/A
6. TRADE NAMES AND SYNONYMS:
Isolatek Mineral Wool

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

INGREDIENT	CAS NUMBER	OSHA PEL	ACGIH TLV-TWA
Mineral Wool	65997-17-3	N/E	1 fiber/cc

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

1. Boiling Point (°F): N/Ap
2. Vapor Pressure (mm Hg): N/Ap
3. Vapor Density (Air=1): N/Ap
4. Solubility in Water: Negligible
5. Specific Gravity (H₂O=1): >1
6. Melting Point (°F): >1800
7. Evaporation Rate: N/Ap
8. Appearance and Odor: White to gray fibrous nodules, low odor.
9. Physical State: Solid

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

1. Flash Point (Method used): N/Ap
2. Flammable Limits: Noncombustible
3. Extinguishing Media: N/Ap
4. Special Fire Fighting Procedures: N/Ap
5. Unusual Fire and Explosion Hazards: None

SECTION V - REACTIVITY DATA

1. Stability: Stable
Conditions to Avoid: Contact with strong acids.
2. Incompatibility (Material to Avoid): N/A
3. Hazardous Decomposition Products: None known.
4. Hazardous Polymerization: N/Ap
Conditions to Avoid: None known.

N/Ap = NOT APPLICABLE

SECTION VI – HEALTH HAZARD DATA

Primary Routes of Entry: Inhalation, Skin and Eye Contact

Acute: Mineral wool may cause transitory skin irritation (itching) and possible irritation of eyes and upper respiratory tract.

Carcinogenicity: NTP - No OSHA - No IARC – 3 (Not classifiable as to human carcinogenicity)

Medical Conditions Aggravated by Exposure: Any condition, which may be aggravated by mechanical irritants.

Emergency and First Aid Procedures:

Eye Contact: *Flush with water.
Skin Contact: *Wash with water. Launder clothing separate from other garments.
Inhalation: *Remove to fresh air.

*If irritation persists, seek medical attention.

USE NORMAL PERSONAL HYGIENE AFTER CONTACT TO REMOVE ANY MATERIAL CONTAMINANTS.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

- Steps to be taken in case material is released or spilled:
Sweep up and place in disposal containers. Avoid inhalation of dust.
- Waste Disposal Method: Land Fill - In accordance with local, state, and federal regulations.
- Precautions to be taken in handling and storing:
Avoid inhalation of dust during use. Avoid skin and eye contact. Use normal personal hygiene to remove material contaminants.

SECTION VIII - CONTROL MEASURES

- Respiratory Protection: Use NIOSH approved dust mask or equivalent for nuisance dust.
- Ventilation: Sufficient to maintain dust levels below TLV.
- Protective Gloves: Wear cloth gloves.
- Eye Protection: Wear protective eye protection.
- Other Protective Equipment: Wear loose fitting long sleeve shirt and pants.

SECTION XI - PREPARATION INFORMATION

Prepared By: Research Department, U.S.A.
Telephone: (973) 347-1200
Effective Date: August 20, 2008

Supersedes: All Previous Issued

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. **VENDOR SPECIFICALLY DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** In no event shall the vendor be liable for special, indirect or consequential damages.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes all risks in his use of the material.