

Y729 - Half-Flange Tip Option
Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W44 x 335	2.25	W1120 x 498	132.8	58.7	3/8	5/8	7/8	1-3/8	1-13/16
290	1.97	432	116.2	67.0	3/8	5/8	7/8	1-3/8	1-13/16
262	1.78	390	105.0	74.2	3/8	5/8	7/8	1-3/8	1-13/16
230	1.58	342	93.2	83.5	3/8	5/8	7/8	1-3/8	1-13/16
W40 x 593	4.03	W1000 x 883	237.8	32.8	5/16	3/8	9/16	15/16	1-5/16
503	3.49	748	205.9	37.8	5/16	3/8	9/16	15/16	1-5/16
431	3.04	641	179.4	43.4	5/16	3/8	9/16	15/16	1-5/16
397	2.80	591	165.2	47.1	5/16	3/8	9/16	15/16	1-5/16
392	3.06	583	180.5	43.1	5/16	3/8	9/16	15/16	1-5/16
372	2.64	554	155.8	50.0	5/16	3/8	9/16	15/16	1-5/16
362	2.57	539	151.6	51.4	5/16	3/8	9/16	15/16	1-5/16
331	2.63	493	155.2	50.2	5/16	3/8	9/16	15/16	1-5/16
327	2.62	487	154.6	50.4	5/16	3/8	9/16	15/16	1-5/16
324	2.31	482	136.3	57.1	3/8	5/8	7/8	1-3/8	1-13/16
297	2.14	442	126.3	61.7	3/8	5/8	7/8	1-3/8	1-13/16
278	2.24	414	132.2	58.9	3/8	5/8	7/8	1-3/8	1-13/16
277	1.99	412	117.4	66.3	3/8	5/8	7/8	1-3/8	1-13/16
264	2.13	393	125.7	62.0	3/8	5/8	7/8	1-3/8	1-13/16
249	1.79	371	105.6	73.7	3/8	5/8	7/8	1-3/8	1-13/16
235	1.90	350	112.1	69.5	3/8	5/8	7/8	1-3/8	1-13/16
215	1.56	320	92.0	84.6	3/8	5/8	7/8	1-3/8	1-13/16
211	1.72	314	101.5	76.7	3/8	5/8	7/8	1-3/8	1-13/16
199	1.45	296	85.6	91.0	5/8	15/16	1-3/16	1-3/4	2-3/8
183	1.50	272	88.5	88.0	3/8	5/8	7/8	1-3/8	1-13/16
167	1.38	249	81.4	95.7	5/8	15/16	1-3/16	1-3/4	2-3/8
149	1.23	222	72.6	107.3	5/8	15/16	1-3/16	1-3/4	2-3/8
W36 x 798	5.36	W920 x 1188	316.2	24.6	5/16	3/8	9/16	15/16	1-5/16
650	4.45	967	262.6	29.7	5/16	3/8	9/16	15/16	1-5/16
527	3.71	784	218.9	35.6	5/16	3/8	9/16	15/16	1-5/16
439	3.14	653	185.3	42.0	5/16	3/8	9/16	15/16	1-5/16
393	2.85	585	168.2	46.3	5/16	3/8	9/16	15/16	1-5/16
359	2.62	534	154.6	50.4	5/16	3/8	9/16	15/16	1-5/16
328	2.39	488	141.0	55.2	3/8	5/8	7/8	1-3/8	1-13/16
300	2.21	446	130.4	59.7	3/8	5/8	7/8	1-3/8	1-13/16
280	2.06	417	121.5	64.1	3/8	5/8	7/8	1-3/8	1-13/16
260	1.93	387	113.9	68.4	3/8	5/8	7/8	1-3/8	1-13/16
256	2.13	381	125.7	62.0	3/8	5/8	7/8	1-3/8	1-13/16
245	1.81	365	106.8	72.9	3/8	5/8	7/8	1-3/8	1-13/16
232	1.93	345	113.9	68.4	3/8	5/8	7/8	1-3/8	1-13/16
230	1.72	342	101.5	76.7	3/8	5/8	7/8	1-3/8	1-13/16
210	1.76	313	103.8	75.0	3/8	5/8	7/8	1-3/8	1-13/16
194	1.63	289	96.2	81.0	3/8	5/8	7/8	1-3/8	1-13/16
182	1.53	271	90.3	86.3	3/8	5/8	7/8	1-3/8	1-13/16
170	1.44	253	85.0	91.7	5/8	15/16	1-3/16	1-3/4	2-3/8
160	1.36	238	80.2	97.1	5/8	15/16	1-3/16	1-3/4	2-3/8
150	1.28	233	75.5	103.1	5/8	15/16	1-3/16	1-3/4	2-3/8

Note: The thickness applied to the flange tips may be reduced to one-half the listed thickness.

Y729 - Half-Flange Tip Option
Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W36 x 135	1.15	W920 x 201	67.9	114.8	5/8	15/16	1-3/16	1-3/4	2-3/8
W33 x 387	2.91	W840 x 576	171.7	45.4	5/16	3/8	9/16	15/16	1-5/16
354	2.68	527	158.1	49.3	5/16	3/8	9/16	15/16	1-5/16
318	2.43	473	143.4	54.3	3/8	5/8	7/8	1-3/8	1-13/16
291	2.24	433	132.2	58.9	3/8	5/8	7/8	1-3/8	1-13/16
263	2.04	392	120.4	64.7	3/8	5/8	7/8	1-3/8	1-13/16
241	1.87	359	110.3	70.6	3/8	5/8	7/8	1-3/8	1-13/16
221	1.73	329	102.1	76.3	3/8	5/8	7/8	1-3/8	1-13/16
201	1.58	299	93.2	83.5	3/8	5/8	7/8	1-3/8	1-13/16
169	1.52	251	89.7	86.8	3/8	5/8	7/8	1-3/8	1-13/16
152	1.37	226	80.8	96.4	5/8	15/16	1-3/16	1-3/4	2-3/8
141	1.28	210	75.5	103.1	5/8	15/16	1-3/16	1-3/4	2-3/8
130	1.18	193	69.6	111.9	5/8	15/16	1-3/16	1-3/4	2-3/8
118	1.08	176	63.7	122.2	5/8	15/16	1-3/16	1-3/4	2-3/8
W30 x 391	3.13	W760 x 582	184.7	42.2	5/16	3/8	9/16	15/16	1-5/16
357	2.88	531	169.9	45.8	5/16	3/8	9/16	15/16	1-5/16
326	2.65	484	156.4	49.8	5/16	3/8	9/16	15/16	1-5/16
292	2.39	434	141.0	55.2	3/8	5/8	7/8	1-3/8	1-13/16
261	2.16	389	127.4	61.1	3/8	5/8	7/8	1-3/8	1-13/16
235	1.96	350	115.6	67.3	3/8	5/8	7/8	1-3/8	1-13/16
211	1.76	314	103.8	75.0	3/8	5/8	7/8	1-3/8	1-13/16
191	1.62	284	95.6	81.5	3/8	5/8	7/8	1-3/8	1-13/16
173	1.45	257	85.6	91.0	5/8	15/16	1-3/16	1-3/4	2-3/8
148	1.47	220	86.7	89.8	3/8	5/8	7/8	1-3/8	1-13/16
132	1.32	196	77.9	100.0	5/8	15/16	1-3/16	1-3/4	2-3/8
124	1.24	185	73.2	106.5	5/8	15/16	1-3/16	1-3/4	2-3/8
116	1.16	173	68.4	113.8	5/8	15/16	1-3/16	1-3/4	2-3/8
108	1.09	161	64.3	121.1	5/8	15/16	1-3/16	1-3/4	2-3/8
99	1	147	59.0	132.0	5/8	15/16	1-3/16	1-3/4	2-3/8
90	0.91	134	53.7	145.1	5/8	15/16	1-3/16	1-3/4	2-3/8
W27x539	4.45	W690 x 802	262.6	29.7	5/16	3/8	9/16	15/16	1-5/16
368	3.17	548	187.0	41.6	5/16	3/8	9/16	15/16	1-5/16
336	2.92	500	172.3	45.2	5/16	3/8	9/16	15/16	1-5/16
307	2.72	457	160.5	48.5	5/16	3/8	9/16	15/16	1-5/16
281	2.49	418	146.9	53.0	3/8	5/8	7/8	1-3/8	1-13/16
258	2.3	384	135.7	57.4	3/8	5/8	7/8	1-3/8	1-13/16
235	2.12	350	125.1	62.3	3/8	5/8	7/8	1-3/8	1-13/16
217	1.97	323	116.2	67.0	3/8	5/8	7/8	1-3/8	1-13/16
194	1.76	289	103.8	75.0	3/8	5/8	7/8	1-3/8	1-13/16
178	1.63	265	96.2	81.0	3/8	5/8	7/8	1-3/8	1-13/16
161	1.48	240	87.3	89.2	3/8	5/8	7/8	1-3/8	1-13/16
146	1.35	217	79.7	97.8	5/8	15/16	1-3/16	1-3/4	2-3/8
129	1.39	192	82.0	95.0	5/8	15/16	1-3/16	1-3/4	2-3/8

Note: The thickness applied to the flange tips may be reduced to one-half the listed thickness.

Y729 - Half-Flange Tip Option
Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W27 x 114	1.23	W690 x 170	72.6	107.3	5/8	15/16	1-3/16	1-3/4	2-3/8
102	1.11	152	65.5	118.9	5/8	15/16	1-3/16	1-3/4	2-3/8
94	1.03	140	60.8	128.2	5/8	15/16	1-3/16	1-3/4	2-3/8
84	0.92	125	54.3	143.5	5/8	15/16	1-3/16	1-3/4	2-3/8
W24 x 370	3.46	W610 x 551	204.1	38.2	5/16	3/8	9/16	15/16	1-5/16
335	3.19	498	188.2	41.4	5/16	3/8	9/16	15/16	1-5/16
306	2.94	455	173.5	44.9	5/16	3/8	9/16	15/16	1-5/16
279	2.71	415	159.9	48.7	5/16	3/8	9/16	15/16	1-5/16
250	2.45	372	144.6	53.9	3/8	5/8	7/8	1-3/8	1-13/16
229	2.27	341	133.9	58.1	3/8	5/8	7/8	1-3/8	1-13/16
207	2.05	307	121.0	64.4	3/8	5/8	7/8	1-3/8	1-13/16
192	1.92	285	113.3	68.8	3/8	5/8	7/8	1-3/8	1-13/16
176	1.77	262	104.4	74.6	3/8	5/8	7/8	1-3/8	1-13/16
162	1.63	241	96.2	81.0	3/8	5/8	7/8	1-3/8	1-13/16
146	1.48	217	87.3	89.2	3/8	5/8	7/8	1-3/8	1-13/16
131	1.33	195	78.5	99.2	5/8	15/16	1-3/16	1-3/4	2-3/8
117	1.2	174	70.8	110.0	5/8	15/16	1-3/16	1-3/4	2-3/8
104	1.07	155	63.1	123.4	5/8	15/16	1-3/16	1-3/4	2-3/8
103	1.25	153	73.8	105.6	5/8	15/16	1-3/16	1-3/4	2-3/8
94	1.14	140	67.3	115.8	5/8	15/16	1-3/16	1-3/4	2-3/8
84	1.02	125	60.2	129.4	5/8	15/16	1-3/16	1-3/4	2-3/8
76	0.93	113	54.9	141.9	5/8	15/16	1-3/16	1-3/4	2-3/8
68	0.83	101	49.0	159.0	11/16	1	1-5/16	1-15/16	2-1/2
62	0.84	92	49.6	157.1	5/8	15/16	1-3/16	1-3/4	2-3/8
55	0.74	82	43.7	178.4	11/16	1	1-5/16	1-15/16	2-1/2
W21 x 201	2.16	W530 x 300	127.4	61.1	3/8	5/8	7/8	1-3/8	1-13/16
182	1.97	272	116.2	67.0	3/8	5/8	7/8	1-3/8	1-13/16
166	1.81	248	106.8	72.9	3/8	5/8	7/8	1-3/8	1-13/16
147	1.61	219	95.0	82.0	3/8	5/8	7/8	1-3/8	1-13/16
132	1.45	196	85.6	91.0	5/8	15/16	1-3/16	1-3/4	2-3/8
122	1.35	182	79.7	97.8	5/8	15/16	1-3/16	1-3/4	2-3/8
111	1.24	165	73.2	106.5	5/8	15/16	1-3/16	1-3/4	2-3/8
101	1.13	150	66.7	116.8	5/8	15/16	1-3/16	1-3/4	2-3/8
93	1.24	138	73.2	106.5	5/8	15/16	1-3/16	1-3/4	2-3/8
83	1.12	123	66.1	117.9	5/8	15/16	1-3/16	1-3/4	2-3/8
73	0.98	109	57.8	134.7	5/8	15/16	1-3/16	1-3/4	2-3/8
68	0.92	101	54.3	143.5	5/8	15/16	1-3/16	1-3/4	2-3/8
62	0.84	92	49.6	157.1	5/8	15/16	1-3/16	1-3/4	2-3/8
57	0.85	85	50.2	155.3	5/8	15/16	1-3/16	1-3/4	2-3/8
55	0.75	82	44.3	176.0	11/16	1	1-5/16	1-15/16	2-1/2
50	0.75	74	44.3	176.0	11/16	1	1-5/16	1-15/16	2-1/2
48	0.66	72	38.9	200.0	3/4	1-1/8	1-7/16	2-1/16	2-11/16
44	0.67	66	39.5	197.0	3/4	1-1/8	1-7/16	2-1/16	2-11/16
W18 x 175	2.12	W460 x 260	125.1	62.3	3/8	5/8	7/8	1-3/8	1-13/16
158	1.93	235	113.9	68.4	3/8	5/8	7/8	1-3/8	1-13/16

Note: The thickness applied to the flange tips may be reduced to one-half the listed thickness.

Y729 - Half-Flange Tip Option
Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W18 x 143	1.77	W460 x 213	104.4	74.6	3/8	5/8	7/8	1-3/8	1-13/16
130	1.61	193	95.0	82.0	3/8	5/8	7/8	1-3/8	1-13/16
119	1.48	177	87.3	89.2	3/8	5/8	7/8	1-3/8	1-13/16
106	1.33	158	78.5	99.2	5/8	15/16	1-3/16	1-3/4	2-3/8
97	1.22	144	72.0	108.2	5/8	15/16	1-3/16	1-3/4	2-3/8
86	1.09	128	64.3	121.1	5/8	15/16	1-3/16	1-3/4	2-3/8
76	0.97	113	57.2	136.1	5/8	15/16	1-3/16	1-3/4	2-3/8
71	1.08	106	63.7	122.2	5/8	15/16	1-3/16	1-3/4	2-3/8
65	0.99	97	58.4	133.3	5/8	15/16	1-3/16	1-3/4	2-3/8
60	0.92	89	54.3	143.5	5/8	15/16	1-3/16	1-3/4	2-3/8
55	0.85	82	50.2	155.3	5/8	15/16	1-3/16	1-3/4	2-3/8
50	0.77	74	45.4	171.4	11/16	1	1-5/16	1-15/16	2-1/2
46	0.78	68	46.0	169.2	11/16	1	1-5/16	1-15/16	2-1/2
40	0.68	60	40.1	194.1	11/16	1	1-5/16	1-15/16	2-1/2
35	0.6	52	35.4	220.0	3/4	1-1/8	1-7/16	2-1/16	2-11/16
W16 x 100	1.37	W410 x 149	80.8	96.4	5/8	15/16	1-3/16	1-3/4	2-3/8
89	1.22	132	72.0	108.2	5/8	15/16	1-3/16	1-3/4	2-3/8
77	1.07	114	63.1	123.4	5/8	15/16	1-3/16	1-3/4	2-3/8
67	0.93	100	54.9	141.9	5/8	15/16	1-3/16	1-3/4	2-3/8
57	0.96	85	56.6	137.5	5/8	15/16	1-3/16	1-3/4	2-3/8
50	0.84	74	49.6	157.1	5/8	15/16	1-3/16	1-3/4	2-3/8
45	0.76	67	44.8	173.7	11/16	1	1-5/16	1-15/16	2-1/2
40	0.68	60	40.1	194.1	11/16	1	1-5/16	1-15/16	2-1/2
36	0.61	53	36.0	216.4	3/4	1-1/8	1-7/16	2-1/16	2-11/16
31	0.59	46	34.8	223.7	3/4	1-1/8	1-7/16	2-1/16	2-11/16
26	0.49	39	28.9	269.4	7/8	1-1/4	1-5/8	2-5/16	3-1/16
W14 x 808	7.28	W360 x 1202	429.5	18.1	5/16	5/16	5/16	7/16	5/8
730	6.76	1086	398.8	19.5	5/16	5/16	5/16	7/16	5/8
665	6.21	990	366.4	21.3	5/16	3/8	9/16	15/16	1-5/16
605	5.82	900	343.4	22.7	5/16	3/8	9/16	15/16	1-5/16
550	5.34	818	315.1	24.7	5/16	3/8	9/16	15/16	1-5/16
500	4.95	744	292.1	26.7	5/16	3/8	9/16	15/16	1-5/16
455	4.59	677	270.8	28.8	5/16	3/8	9/16	15/16	1-5/16
426	4.32	634	254.9	30.6	5/16	3/8	9/16	15/16	1-5/16
398	4.09	592	241.3	32.3	5/16	3/8	9/16	15/16	1-5/16
370	3.84	551	226.6	34.4	5/16	3/8	9/16	15/16	1-5/16
342	3.58	509	211.2	36.9	5/16	3/8	9/16	15/16	1-5/16
311	3.3	463	194.7	40.0	5/16	3/8	9/16	15/16	1-5/16
283	3.03	421	178.8	43.6	5/16	3/8	9/16	15/16	1-5/16
257	2.78	382	164.0	47.5	5/16	3/8	9/16	15/16	1-5/16
233	2.55	347	150.5	51.8	5/16	3/8	9/16	15/16	1-5/16
211	2.32	314	136.9	56.9	3/8	5/8	7/8	1-3/8	1-13/16
193	2.14	287	126.3	61.7	3/8	5/8	7/8	1-3/8	1-13/16
176	1.96	262	115.6	67.3	3/8	5/8	7/8	1-3/8	1-13/16
159	1.78	237	105.0	74.2	3/8	5/8	7/8	1-3/8	1-13/16
145	1.64	216	96.8	80.5	3/8	5/8	7/8	1-3/8	1-13/16
132	1.56	196	92.0	84.6	3/8	5/8	7/8	1-3/8	1-13/16

Note: The thickness applied to the flange tips may be reduced to one-half the listed thickness.

Y729 - Half-Flange Tip Option
Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W14 x 120	1.42	W360 x 179	83.8	93.0	5/8	15/16	1-3/16	1-3/4	2-3/8
109	1.29	162	76.1	102.3	5/8	15/16	1-3/16	1-3/4	2-3/8
99	1.18	147	69.6	111.9	5/8	15/16	1-3/16	1-3/4	2-3/8
90	1.08	134	63.7	122.2	5/8	15/16	1-3/16	1-3/4	2-3/8
82	1.23	122	72.6	107.3	5/8	15/16	1-3/16	1-3/4	2-3/8
74	1.12	110	66.1	117.9	5/8	15/16	1-3/16	1-3/4	2-3/8
68	1.04	101	61.4	126.9	5/8	15/16	1-3/16	1-3/4	2-3/8
61	0.92	91	54.3	143.5	5/8	15/16	1-3/16	1-3/4	2-3/8
53	0.91	79	53.7	145.1	5/8	15/16	1-3/16	1-3/4	2-3/8
48	0.83	72	49.0	159.0	11/16	1	1-5/16	1-15/16	2-1/2
43	0.75	64	44.3	176.0	11/16	1	1-5/16	1-15/16	2-1/2
38	0.7	57	41.3	188.6	11/16	1	1-5/16	1-15/16	2-1/2
34	0.63	51	37.2	209.5	3/4	1-1/8	1-7/16	2-1/16	2-11/16
30	0.56	45	33.0	235.7	7/8	1-1/4	1-5/8	2-5/16	3-1/16
26	0.55	39	32.5	240.0	7/8	1-1/4	1-5/8	2-5/16	3-1/16
22	0.47	33	27.7	280.9	7/8	1-1/4	1-5/8	2-5/16	3-1/16
W12 x 336	4.06	W310 x 500	239.5	32.5	5/16	3/8	9/16	15/16	1-5/16
305	3.76	454	221.8	35.1	5/16	3/8	9/16	15/16	1-5/16
279	3.5	415	206.5	37.7	5/16	3/8	9/16	15/16	1-5/16
252	3.2	375	188.8	41.3	5/16	3/8	9/16	15/16	1-5/16
230	2.96	342	174.6	44.6	5/16	3/8	9/16	15/16	1-5/16
210	2.73	313	161.1	48.4	5/16	3/8	9/16	15/16	1-5/16
190	2.5	283	147.5	52.8	3/8	5/8	7/8	1-3/8	1-13/16
170	2.26	253	133.3	58.4	3/8	5/8	7/8	1-3/8	1-13/16
152	2.04	225	120.4	64.7	3/8	5/8	7/8	1-3/8	1-13/16
136	1.86	202	109.7	71.0	3/8	5/8	7/8	1-3/8	1-13/16
120	1.65	179	97.4	80.0	3/8	5/8	7/8	1-3/8	1-13/16
106	1.47	158	86.7	89.8	3/8	5/8	7/8	1-3/8	1-13/16
96	1.34	143	79.1	98.5	5/8	15/16	1-3/16	1-3/4	2-3/8
87	1.22	129	72.0	108.2	5/8	15/16	1-3/16	1-3/4	2-3/8
79	1.11	117	65.5	118.9	5/8	15/16	1-3/16	1-3/4	2-3/8
72	1.02	107	60.2	129.4	5/8	15/16	1-3/16	1-3/4	2-3/8
65	0.92	97	54.3	143.5	5/8	15/16	1-3/16	1-3/4	2-3/8
58	0.92	86	54.3	143.5	5/8	15/16	1-3/16	1-3/4	2-3/8
53	0.85	79	50.2	155.3	5/8	15/16	1-3/16	1-3/4	2-3/8
50	0.9	74	53.1	146.7	5/8	15/16	1-3/16	1-3/4	2-3/8
45	0.82	67	48.4	161.0	11/16	1	1-5/16	1-15/16	2-1/2
40	0.73	60	43.1	180.8	11/16	1	1-5/16	1-15/16	2-1/2
35	0.7	52	41.3	188.6	11/16	1	1-5/16	1-15/16	2-1/2
30	0.6	45	35.4	220.0	3/4	1-1/8	1-7/16	2-1/16	2-11/16
26	0.53	39	31.3	249.1	7/8	1-1/4	1-5/8	2-5/16	3-1/16
22	0.56	33	33.0	235.7	7/8	1-1/4	1-5/8	2-5/16	3-1/16
19	0.48	28	28.3	275.0	7/8	1-1/4	1-5/8	2-5/16	3-1/16
16	0.41	24	24.2	322.0	1	1-3/8	1-3/4	2-7/16	3-1/8
14	0.36	25	21.2	366.7	1	1-3/8	1-3/4	2-7/16	3-1/8
W10 x 112	1.81	W250 x 167	106.8	72.9	3/8	5/8	7/8	1-3/8	1-13/16
100	1.64	149	96.8	80.5	3/8	5/8	7/8	1-3/8	1-13/16

Note: The thickness applied to the flange tips may be reduced to one-half the listed thickness.

Y729 - Half-Flange Tip Option
Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W10 x 88	1.45	W250 x 131	85.6	91.0	5/8	15/16	1-3/16	1-3/4	2-3/8
77	1.28	115	75.5	103.1	5/8	15/16	1-3/16	1-3/4	2-3/8
68	1.15	101	67.9	114.8	5/8	15/16	1-3/16	1-3/4	2-3/8
60	1.01	89	59.6	130.7	5/8	15/16	1-3/16	1-3/4	2-3/8
54	0.92	80	54.3	143.5	5/8	15/16	1-3/16	1-3/4	2-3/8
49	0.84	73	49.6	157.1	5/8	15/16	1-3/16	1-3/4	2-3/8
45	0.88	67	51.9	150.0	5/8	15/16	1-3/16	1-3/4	2-3/8
39	0.78	58	46.0	169.2	11/16	1	1-5/16	1-15/16	2-1/2
33	0.66	49	38.9	200.0	3/4	1-1/8	1-7/16	2-1/16	2-11/16
30	0.69	45	40.7	191.3	11/16	1	1-5/16	1-15/16	2-1/2
26	0.61	39	36.0	216.4	3/4	1-1/8	1-7/16	2-1/16	2-11/16
22	0.52	33	30.7	253.8	7/8	1-1/4	1-5/8	2-5/16	3-1/16
19	0.53	28	31.3	249.1	7/8	1-1/4	1-5/8	2-5/16	3-1/16
17	0.48	25	28.3	275.0	7/8	1-1/4	1-5/8	2-5/16	3-1/16
15	0.42	22	24.8	314.3	1	1-3/8	1-3/4	2-7/16	3-1/8
12	0.34	18	20.1	388.2	1	1-3/8	1-3/4	2-7/16	3-1/8
W8 x 67	1.37	W200 x 100	80.8	96.4	5/8	15/16	1-3/16	1-3/4	2-3/8
58	1.2	86	70.8	110.0	5/8	15/16	1-3/16	1-3/4	2-3/8
48	1	71	59.0	132.0	5/8	15/16	1-3/16	1-3/4	2-3/8
40	0.84	59	49.6	157.1	5/8	15/16	1-3/16	1-3/4	2-3/8
35	0.74	52	43.7	178.4	11/16	1	1-5/16	1-15/16	2-1/2
31	0.66	46	38.9	200.0	3/4	1-1/8	1-7/16	2-1/16	2-11/16
28	0.68	42	40.1	194.1	11/16	1	1-5/16	1-15/16	2-1/2
24	0.59	36	34.8	223.7	3/4	1-1/8	1-7/16	2-1/16	2-11/16
21	0.57	31	33.6	231.6	7/8	1-1/4	1-5/8	2-5/16	3-1/16
18	0.49	27	28.9	269.4	7/8	1-1/4	1-5/8	2-5/16	3-1/16
15	0.48	22	28.3	275.0	7/8	1-1/4	1-5/8	2-5/16	3-1/16
13	0.42	19	24.8	314.3	1	1-3/8	1-3/4	2-7/16	3-1/8
10	0.33	15	19.5	400.0	1	1-3/8	1-3/4	2-7/16	3-1/8
W6 x 25	0.69	W150 x 37	40.7	191.3	11/16	1	1-5/16	1-15/16	2-1/2
20	0.56	30	33.0	235.7	7/8	1-1/4	1-5/8	2-5/16	3-1/16
16	0.58	24	34.2	227.6	3/4	1-1/8	1-7/16	2-1/16	2-11/16
15	0.43	22	25.4	307.0	1	1-3/8	1-3/4	2-7/16	3-1/8
12	0.44	18	26.0	300.0	7/8	1-1/4	1-5/8	2-5/16	3-1/16
9	0.33	14	19.5	400.0	1	1-3/8	1-3/4	2-7/16	3-1/8
W5 x 19	0.64	W130 x 28	37.8	206.3	3/4	1-1/8	1-7/16	2-1/16	2-11/16
16	0.55	24	32.5	240.0	7/8	1-1/4	1-5/8	2-5/16	3-1/16
W4 x 13	0.55	W100 x 19	32.5	240.0	7/8	1-1/4	1-5/8	2-5/16	3-1/16

Note: The thickness applied to the flange tips may be reduced to one-half the listed thickness.