

Y729

Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W44 x 335	2.25	W1120 x 498	132.8	58.7	1/4	1/2	5/8	15/16	1-1/4
290	1.97	432	116.2	67.0	1/4	9/16	11/16	1-1/16	1-3/8
262	1.78	390	105.0	74.2	1/4	9/16	3/4	1-1/8	1-1/2
230	1.58	342	93.2	83.5	1/4	9/16	13/16	1-1/4	1-5/8
W40 x 593	4.03	W1000 x 883	237.8	32.8	1/4	5/16	7/16	5/8	13/16
503	3.49	748	205.9	37.8	1/4	3/8	7/16	11/16	7/8
431	3.04	641	179.4	43.4	1/4	3/8	1/2	3/4	1
397	2.80	591	165.2	47.1	1/4	7/16	9/16	13/16	1-1/8
392	3.06	583	180.5	43.1	1/4	3/8	1/2	3/4	1
372	2.64	554	155.8	50.0	1/4	7/16	5/8	7/8	1-3/16
362	2.57	539	151.6	51.4	1/4	7/16	5/8	7/8	1-3/16
331	2.63	493	155.2	50.2	1/4	7/16	5/8	7/8	1-3/16
327	2.62	487	154.6	50.4	1/4	7/16	5/8	7/8	1-3/16
324	2.31	482	136.3	57.1	1/4	1/2	5/8	15/16	1-3/16
297	2.14	442	126.3	61.7	1/4	1/2	5/8	15/16	1-1/4
278	2.24	414	132.2	58.9	1/4	1/2	5/8	15/16	1-1/4
277	1.99	412	117.4	66.3	1/4	1/2	11/16	1	1-3/8
264	2.13	393	125.7	62.0	1/4	1/2	11/16	1	1-5/16
249	1.79	371	105.6	73.7	1/4	9/16	3/4	1-1/8	1-1/2
235	1.90	350	112.1	69.5	1/4	9/16	3/4	1-1/16	1-7/16
215	1.56	320	92.0	84.6	1/4	9/16	13/16	1-1/4	1-5/8
211	1.72	314	101.5	76.7	1/4	9/16	3/4	1-1/8	1-1/2
199	1.45	296	85.6	91.0	7/16	11/16	7/8	1-5/16	1-3/4
183	1.50	272	88.5	88.0	1/4	9/16	13/16	1-1/4	1-11/16
167	1.38	249	81.4	95.7	7/16	11/16	15/16	1-3/8	1-13/16
149	1.23	222	72.6	107.3	7/16	3/4	1	1-1/2	1-15/16
W36 x 798	5.36	W920 x 1188	316.2	24.6	1/4	1/4	5/16	7/16	5/8
650	4.45	967	262.6	29.7	1/4	5/16	3/8	9/16	3/4
527	3.71	784	218.9	35.6	1/4	5/16	7/16	5/8	7/8
439	3.14	653	185.3	42.0	1/4	3/8	1/2	3/4	1
393	2.85	585	168.2	46.3	1/4	7/16	9/16	13/16	1-1/16
359	2.62	534	154.6	50.4	1/4	7/16	5/8	7/8	1-3/16
328	2.39	488	141.0	55.2	1/4	7/16	5/8	7/8	1-3/16
300	2.21	446	130.4	59.7	1/4	1/2	5/8	15/16	1-1/4
280	2.06	417	121.5	64.1	1/4	1/2	11/16	1	1-5/16
260	1.93	387	113.9	68.4	1/4	9/16	11/16	1-1/16	1-3/8
256	2.13	381	125.7	62.0	1/4	1/2	11/16	1	1-5/16
245	1.81	365	106.8	72.9	1/4	9/16	3/4	1-1/8	1-7/16
232	1.93	345	113.9	68.4	1/4	9/16	11/16	1-1/16	1-3/8
230	1.72	342	101.5	76.7	1/4	9/16	3/4	1-1/8	1-1/2
210	1.76	313	103.8	75.0	1/4	9/16	3/4	1-1/8	1-1/2
194	1.63	289	96.2	81.0	1/4	9/16	13/16	1-3/16	1-9/16
182	1.53	271	90.3	86.3	1/4	9/16	13/16	1-1/4	1-11/16
170	1.44	253	85.0	91.7	7/16	11/16	7/8	1-5/16	1-3/4
160	1.36	238	80.2	97.1	7/16	11/16	15/16	1-3/8	1-13/16
150	1.28	233	75.5	103.1	7/16	3/4	15/16	1-7/16	1-7/8

Note: Increased thickness may be applied when thickness applied to lower flange tips is reduced by one-half.

Y729

Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W36 x 135	1.15	W920 x 201	67.9	114.8	7/16	13/16	1-1/16	1-9/16	2-1/16
W33 x 387	2.91	W840 x 576	171.7	45.4	1/4	7/16	9/16	13/16	1-1/16
354	2.68	527	158.1	49.3	1/4	7/16	9/16	7/8	1-1/8
318	2.43	473	143.4	54.3	1/4	7/16	9/16	7/8	1-1/8
291	2.24	433	132.2	58.9	1/4	1/2	5/8	15/16	1-1/4
263	2.04	392	120.4	64.7	1/4	1/2	11/16	1	1-5/16
241	1.87	359	110.3	70.6	1/4	9/16	3/4	1-1/16	1-7/16
221	1.73	329	102.1	76.3	1/4	9/16	3/4	1-1/8	1-1/2
201	1.58	299	93.2	83.5	1/4	9/16	13/16	1-1/4	1-5/8
169	1.52	251	89.7	86.8	1/4	9/16	13/16	1-1/4	1-11/16
152	1.37	226	80.8	96.4	7/16	11/16	15/16	1-3/8	1-13/16
141	1.28	210	75.5	103.1	7/16	3/4	15/16	1-7/16	1-7/8
130	1.18	193	69.6	111.9	7/16	3/4	1	1-1/2	2
118	1.08	176	63.7	122.2	7/16	13/16	1-1/16	1-5/8	2-1/8
W30 x 391	3.13	W760 x 582	184.7	42.2	1/4	3/8	1/2	3/4	1
357	2.88	531	169.9	45.8	1/4	7/16	9/16	13/16	1-1/16
326	2.65	484	156.4	49.8	1/4	7/16	9/16	7/8	1-1/8
292	2.39	434	141.0	55.2	1/4	7/16	5/8	7/8	1-3/16
261	2.16	389	127.4	61.1	1/4	1/2	5/8	15/16	1-1/4
235	1.96	350	115.6	67.3	1/4	9/16	11/16	1-1/16	1-3/8
211	1.76	314	103.8	75.0	1/4	9/16	3/4	1-1/8	1-1/2
191	1.62	284	95.6	81.5	1/4	9/16	13/16	1-3/16	1-5/8
173	1.45	257	85.6	91.0	7/16	11/16	7/8	1-5/16	1-3/4
148	1.47	220	86.7	89.8	1/4	9/16	13/16	1-1/4	1-11/16
132	1.32	196	77.9	100.0	7/16	11/16	15/16	1-3/8	1-7/8
124	1.24	185	73.2	106.5	7/16	3/4	1	1-1/2	1-15/16
116	1.16	173	68.4	113.8	7/16	13/16	1-1/16	1-9/16	2-1/16
108	1.09	161	64.3	121.1	7/16	13/16	1-1/16	1-5/8	2-1/8
99	1	147	59.0	132.0	7/16	13/16	1-1/8	1-5/8	2-1/8
90	0.91	134	53.7	145.1	7/16	13/16	1-1/8	1-5/8	2-1/8
W27x539	4.45	W690 x 802	262.6	29.7	1/4	5/16	3/8	9/16	3/4
368	3.17	548	187.0	41.6	1/4	3/8	1/2	3/4	1
336	2.92	500	172.3	45.2	1/4	7/16	9/16	13/16	1-1/16
307	2.72	457	160.5	48.5	1/4	7/16	9/16	7/8	1-1/8
281	2.49	418	146.9	53.0	1/4	7/16	9/16	7/8	1-1/8
258	2.3	384	135.7	57.4	1/4	1/2	5/8	15/16	1-3/16
235	2.12	350	125.1	62.3	1/4	1/2	11/16	1	1-5/16
217	1.97	323	116.2	67.0	1/4	9/16	11/16	1-1/16	1-3/8
194	1.76	289	103.8	75.0	1/4	9/16	3/4	1-1/8	1-1/2
178	1.63	265	96.2	81.0	1/4	9/16	13/16	1-3/16	1-9/16
161	1.48	240	87.3	89.2	1/4	9/16	13/16	1-1/4	1-11/16
146	1.35	217	79.7	97.8	7/16	11/16	15/16	1-3/8	1-13/16
129	1.39	192	82.0	95.0	7/16	11/16	15/16	1-3/8	1-13/16

Note: Increased thickness may be applied when thickness applied to lower flange tips is reduced by one-half.

Y729

Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W27 x 114	1.23	W690 x 170	72.6	107.3	7/16	3/4	1	1-1/2	1-15/16
102	1.11	152	65.5	118.9	7/16	13/16	1-1/16	1-9/16	2-1/8
94	1.03	140	60.8	128.2	7/16	13/16	1-1/8	1-5/8	2-1/8
84	0.92	125	54.3	143.5	7/16	13/16	1-1/8	1-5/8	2-1/8
W24 x 370	3.46	W610 x 551	204.1	38.2	1/4	3/8	7/16	11/16	7/8
335	3.19	498	188.2	41.4	1/4	3/8	1/2	3/4	1
306	2.94	455	173.5	44.9	1/4	7/16	9/16	13/16	1-1/16
279	2.71	415	159.9	48.7	1/4	7/16	9/16	7/8	1-1/8
250	2.45	372	144.6	53.9	1/4	7/16	9/16	7/8	1-1/8
229	2.27	341	133.9	58.1	1/4	1/2	5/8	15/16	1-3/16
207	2.05	307	121.0	64.4	1/4	1/2	11/16	1	1-5/16
192	1.92	285	113.3	68.8	1/4	9/16	11/16	1-1/16	1-3/8
176	1.77	262	104.4	74.6	1/4	9/16	3/4	1-1/8	1-1/2
162	1.63	241	96.2	81.0	1/4	9/16	13/16	1-3/16	1-9/16
146	1.48	217	87.3	89.2	1/4	9/16	13/16	1-1/4	1-11/16
131	1.33	195	78.5	99.2	7/16	11/16	15/16	1-3/8	1-7/8
117	1.2	174	70.8	110.0	7/16	3/4	1	1-1/2	2
104	1.07	155	63.1	123.4	7/16	13/16	1-1/8	1-5/8	2-1/8
103	1.25	153	73.8	105.6	7/16	3/4	1	1-7/16	1-15/16
94	1.14	140	67.3	115.8	7/16	13/16	1-1/16	1-9/16	2-1/16
84	1.02	125	60.2	129.4	7/16	13/16	1-1/8	1-5/8	2-1/8
76	0.93	113	54.9	141.9	7/16	13/16	1-1/8	1-5/8	2-1/8
68	0.83	101	49.0	159.0	7/16	13/16	1-1/8	1-5/8	2-1/8
62	0.84	92	49.6	157.1	7/16	13/16	1-1/8	1-5/8	2-1/8
55	0.74	82	43.7	178.4	9/16	15/16	1-1/4	1-13/16	2-5/16
W21 x 201	2.16	W530 x 300	127.4	61.1	1/4	1/2	5/8	15/16	1-1/4
182	1.97	272	116.2	67.0	1/4	9/16	11/16	1-1/16	1-3/8
166	1.81	248	106.8	72.9	1/4	9/16	3/4	1-1/8	1-7/16
147	1.61	219	95.0	82.0	1/4	9/16	13/16	1-3/16	1-5/8
132	1.45	196	85.6	91.0	7/16	11/16	7/8	1-5/16	1-3/4
122	1.35	182	79.7	97.8	7/16	11/16	15/16	1-3/8	1-13/16
111	1.24	165	73.2	106.5	7/16	3/4	1	1-1/2	1-15/16
101	1.13	150	66.7	116.8	7/16	13/16	1-1/16	1-9/16	2-1/16
93	1.24	138	73.2	106.5	7/16	3/4	1	1-1/2	1-15/16
83	1.12	123	66.1	117.9	7/16	13/16	1-1/16	1-9/16	2-1/8
73	0.98	109	57.8	134.7	7/16	13/16	1-1/8	1-5/8	2-1/8
68	0.92	101	54.3	143.5	7/16	13/16	1-1/8	1-5/8	2-1/8
62	0.84	92	49.6	157.1	7/16	13/16	1-1/8	1-5/8	2-1/8
57	0.85	85	50.2	155.3	7/16	13/16	1-1/8	1-5/8	2-1/8
55	0.75	82	44.3	176.0	9/16	15/16	1-1/4	1-13/16	2-5/16
50	0.75	74	44.3	176.0	9/16	15/16	1-1/4	1-13/16	2-5/16
48	0.66	72	38.9	200.0	5/8	1	1-5/16	1-7/8	2-3/8
44	0.67	66	39.5	197.0	5/8	1	1-5/16	1-7/8	2-3/8
W18 x 175	2.12	W460 x 260	125.1	62.3	1/4	1/2	11/16	1	1-5/16
158	1.93	235	113.9	68.4	1/4	9/16	11/16	1-1/16	1-3/8

Note: Increased thickness may be applied when thickness applied to lower flange tips is reduced by one-half.

Y729

Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W18 x 143	1.77	W460 x 213	104.4	74.6	1/4	9/16	3/4	1-1/8	1-1/2
130	1.61	193	95.0	82.0	1/4	9/16	13/16	1-3/16	1-5/8
119	1.48	177	87.3	89.2	1/4	9/16	13/16	1-1/4	1-11/16
106	1.33	158	78.5	99.2	7/16	11/16	15/16	1-3/8	1-7/8
97	1.22	144	72.0	108.2	7/16	3/4	1	1-1/2	2
86	1.09	128	64.3	121.1	7/16	13/16	1-1/16	1-5/8	2-1/8
76	0.97	113	57.2	136.1	7/16	13/16	1-1/8	1-5/8	2-1/8
71	1.08	106	63.7	122.2	7/16	13/16	1-1/16	1-5/8	2-1/8
65	0.99	97	58.4	133.3	7/16	13/16	1-1/8	1-5/8	2-1/8
60	0.92	89	54.3	143.5	7/16	13/16	1-1/8	1-5/8	2-1/8
55	0.85	82	50.2	155.3	7/16	13/16	1-1/8	1-5/8	2-1/8
50	0.77	74	45.4	171.4	9/16	15/16	1-1/4	1-13/16	2-5/16
46	0.78	68	46.0	169.2	9/16	15/16	1-1/4	1-13/16	2-5/16
40	0.68	60	40.1	194.1	9/16	15/16	1-1/4	1-13/16	2-5/16
35	0.6	52	35.4	220.0	5/8	1	1-5/16	1-7/8	2-3/8
W16 x 100	1.37	W410 x 149	80.8	96.4	7/16	11/16	15/16	1-3/8	1-13/16
89	1.22	132	72.0	108.2	7/16	3/4	1	1-1/2	2
77	1.07	114	63.1	123.4	7/16	13/16	1-1/8	1-5/8	2-1/8
67	0.93	100	54.9	141.9	7/16	13/16	1-1/8	1-5/8	2-1/8
57	0.96	85	56.6	137.5	7/16	13/16	1-1/8	1-5/8	2-1/8
50	0.84	74	49.6	157.1	7/16	13/16	1-1/8	1-5/8	2-1/8
45	0.76	67	44.8	173.7	9/16	15/16	1-1/4	1-13/16	2-5/16
40	0.68	60	40.1	194.1	9/16	15/16	1-1/4	1-13/16	2-5/16
36	0.61	53	36.0	216.4	5/8	1	1-5/16	1-7/8	2-3/8
31	0.59	46	34.8	223.7	5/8	1	1-5/16	1-7/8	2-3/8
26	0.49	39	28.9	269.4	13/16	1-1/8	1-7/16	2	2-9/16
W14 x 808	7.28	W360 x 1202	429.5	18.1	1/4	1/4	1/4	3/8	7/16
730	6.76	1086	398.8	19.5	1/4	1/4	1/4	3/8	1/2
665	6.21	990	366.4	21.3	1/4	1/4	1/4	3/8	1/2
605	5.82	900	343.4	22.7	1/4	1/4	5/16	7/16	9/16
550	5.34	818	315.1	24.7	1/4	1/4	5/16	7/16	5/8
500	4.95	744	292.1	26.7	1/4	1/4	5/16	1/2	5/8
455	4.59	677	270.8	28.8	1/4	5/16	3/8	9/16	11/16
426	4.32	634	254.9	30.6	1/4	5/16	3/8	9/16	3/4
398	4.09	592	241.3	32.3	1/4	5/16	3/8	9/16	3/4
370	3.84	551	226.6	34.4	1/4	5/16	7/16	5/8	13/16
342	3.58	509	211.2	36.9	1/4	3/8	7/16	11/16	7/8
311	3.3	463	194.7	40.0	1/4	3/8	1/2	11/16	15/16
283	3.03	421	178.8	43.6	1/4	3/8	1/2	3/4	1
257	2.78	382	164.0	47.5	1/4	7/16	9/16	13/16	1-1/8
233	2.55	347	150.5	51.8	1/4	7/16	5/8	7/8	1-3/16
211	2.32	314	136.9	56.9	1/4	7/16	5/8	7/8	1-3/16
193	2.14	287	126.3	61.7	1/4	1/2	5/8	15/16	1-1/4
176	1.96	262	115.6	67.3	1/4	9/16	11/16	1-1/16	1-3/8
159	1.78	237	105.0	74.2	1/4	9/16	3/4	1-1/8	1-1/2
145	1.64	216	96.8	80.5	1/4	9/16	13/16	1-3/16	1-9/16
132	1.56	196	92.0	84.6	1/4	9/16	13/16	1-1/4	1-5/8

Note: Increased thickness may be applied when thickness applied to lower flange tips is reduced by one-half.

Y729

Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W14 x 120	1.42	W360 x 179	83.8	93.0	7/16	11/16	7/8	1-5/16	1-3/4
109	1.29	162	76.1	102.3	7/16	3/4	15/16	1-7/16	1-7/8
99	1.18	147	69.6	111.9	7/16	3/4	1	1-1/2	2
90	1.08	134	63.7	122.2	7/16	13/16	1-1/16	1-5/8	2-1/8
82	1.23	122	72.6	107.3	7/16	3/4	1	1-1/2	1-15/16
74	1.12	110	66.1	117.9	7/16	13/16	1-1/16	1-9/16	2-1/8
68	1.04	101	61.4	126.9	7/16	13/16	1-1/8	1-5/8	2-1/8
61	0.92	91	54.3	143.5	7/16	13/16	1-1/8	1-5/8	2-1/8
53	0.91	79	53.7	145.1	7/16	13/16	1-1/8	1-5/8	2-1/8
48	0.83	72	49.0	159.0	7/16	13/16	1-1/8	1-5/8	2-1/8
43	0.75	64	44.3	176.0	9/16	15/16	1-1/4	1-13/16	2-5/16
38	0.7	57	41.3	188.6	9/16	15/16	1-1/4	1-13/16	2-5/16
34	0.63	51	37.2	209.5	5/8	1	1-5/16	1-7/8	2-3/8
30	0.56	45	33.0	235.7	13/16	1-1/8	1-7/16	2	2-9/16
26	0.55	39	32.5	240.0	13/16	1-1/8	1-7/16	2	2-9/16
22	0.47	33	27.7	280.9	13/16	1-1/8	1-7/16	2	2-9/16
W12 x 336	4.06	W310 x 500	239.5	32.5	1/4	5/16	7/16	5/8	13/16
305	3.76	454	221.8	35.1	1/4	5/16	7/16	5/8	13/16
279	3.5	415	206.5	37.7	1/4	3/8	7/16	11/16	7/8
252	3.2	375	188.8	41.3	1/4	3/8	1/2	3/4	1
230	2.96	342	174.6	44.6	1/4	7/16	9/16	13/16	1-1/16
210	2.73	313	161.1	48.4	1/4	7/16	9/16	7/8	1-1/8
190	2.5	283	147.5	52.8	1/4	7/16	9/16	7/8	1-1/8
170	2.26	253	133.3	58.4	1/4	1/2	5/8	15/16	1-1/4
152	2.04	225	120.4	64.7	1/4	1/2	11/16	1	1-5/16
136	1.86	202	109.7	71.0	1/4	9/16	3/4	1-1/16	1-7/16
120	1.65	179	97.4	80.0	1/4	9/16	13/16	1-3/16	1-9/16
106	1.47	158	86.7	89.8	1/4	9/16	13/16	1-1/4	1-11/16
96	1.34	143	79.1	98.5	7/16	11/16	15/16	1-3/8	1-13/16
87	1.22	129	72.0	108.2	7/16	3/4	1	1-1/2	2
79	1.11	117	65.5	118.9	7/16	13/16	1-1/16	1-9/16	2-1/8
72	1.02	107	60.2	129.4	7/16	13/16	1-1/8	1-5/8	2-1/8
65	0.92	97	54.3	143.5	7/16	13/16	1-1/8	1-5/8	2-1/8
58	0.92	86	54.3	143.5	7/16	13/16	1-1/8	1-5/8	2-1/8
53	0.85	79	50.2	155.3	7/16	13/16	1-1/8	1-5/8	2-1/8
50	0.9	74	53.1	146.7	7/16	13/16	1-1/8	1-5/8	2-1/8
45	0.82	67	48.4	161.0	9/16	15/16	1-1/4	1-13/16	2-5/16
40	0.73	60	43.1	180.8	9/16	15/16	1-1/4	1-13/16	2-5/16
35	0.7	52	41.3	188.6	9/16	15/16	1-1/4	1-13/16	2-5/16
30	0.6	45	35.4	220.0	5/8	1	1-5/16	1-7/8	2-3/8
26	0.53	39	31.3	249.1	13/16	1-1/8	1-7/16	2	2-9/16
22	0.56	33	33.0	235.7	13/16	1-1/8	1-7/16	2	2-9/16
19	0.48	28	28.3	275.0	13/16	1-1/8	1-7/16	2	2-9/16
16	0.41	24	24.2	322.0	15/16	1-1/4	1-9/16	2-1/8	2-11/16
14	0.36	25	21.2	366.7	15/16	1-1/4	1-9/16	2-1/8	2-11/16
W10 x 112	1.81	W250 x 167	106.8	72.9	1/4	9/16	3/4	1-1/8	1-7/16
100	1.64	149	96.8	80.5	1/4	9/16	13/16	1-3/16	1-9/16

Note: Increased thickness may be applied when thickness applied to lower flange tips is reduced by one-half.

Y729

Wide Flange Structural Steel Columns
CAFCO 300, 300ES, 300SB

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
W10 x 88	1.45	W250 x 131	85.6	91.0	7/16	11/16	7/8	1-5/16	1-3/4
77	1.28	115	75.5	103.1	7/16	3/4	15/16	1-7/16	1-7/8
68	1.15	101	67.9	114.8	7/16	13/16	1-1/16	1-9/16	2-1/16
60	1.01	89	59.6	130.7	7/16	13/16	1-1/8	1-5/8	2-1/8
54	0.92	80	54.3	143.5	7/16	13/16	1-1/8	1-5/8	2-1/8
49	0.84	73	49.6	157.1	7/16	13/16	1-1/8	1-5/8	2-1/8
45	0.88	67	51.9	150.0	7/16	13/16	1-1/8	1-5/8	2-1/8
39	0.78	58	46.0	169.2	9/16	15/16	1-1/4	1-13/16	2-5/16
33	0.66	49	38.9	200.0	5/8	1	1-5/16	1-7/8	2-3/8
30	0.69	45	40.7	191.3	9/16	15/16	1-1/4	1-13/16	2-5/16
26	0.61	39	36.0	216.4	5/8	1	1-5/16	1-7/8	2-3/8
22	0.52	33	30.7	253.8	13/16	1-1/8	1-7/16	2	2-9/16
19	0.53	28	31.3	249.1	13/16	1-1/8	1-7/16	2	2-9/16
17	0.48	25	28.3	275.0	13/16	1-1/8	1-7/16	2	2-9/16
15	0.42	22	24.8	314.3	15/16	1-1/4	1-9/16	2-1/8	2-11/16
12	0.34	18	20.1	388.2	15/16	1-1/4	1-9/16	2-1/8	2-11/16
W8 x 67	1.37	W200 x 100	80.8	96.4	7/16	11/16	15/16	1-3/8	1-13/16
58	1.2	86	70.8	110.0	7/16	3/4	1	1-1/2	2
48	1	71	59.0	132.0	7/16	13/16	1-1/8	1-5/8	2-1/8
40	0.84	59	49.6	157.1	7/16	13/16	1-1/8	1-5/8	2-1/8
35	0.74	52	43.7	178.4	9/16	15/16	1-1/4	1-13/16	2-5/16
31	0.66	46	38.9	200.0	5/8	1	1-5/16	1-7/8	2-3/8
28	0.68	42	40.1	194.1	9/16	15/16	1-1/4	1-13/16	2-5/16
24	0.59	36	34.8	223.7	5/8	1	1-5/16	1-7/8	2-3/8
21	0.57	31	33.6	231.6	5/8	1	1-5/16	1-7/8	2-3/8
18	0.49	27	28.9	269.4	13/16	1-1/8	1-7/16	2	2-9/16
15	0.48	22	28.3	275.0	13/16	1-1/8	1-7/16	2	2-9/16
13	0.42	19	24.8	314.3	15/16	1-1/4	1-9/16	2-1/8	2-11/16
10	0.33	15	19.5	400.0	15/16	1-1/4	1-9/16	2-1/8	2-11/16
W6 x 25	0.69	W150 x 37	40.7	191.3	9/16	15/16	1-1/4	1-13/16	2-5/16
20	0.56	30	33.0	235.7	13/16	1-1/8	1-7/16	2	2-9/16
16	0.58	24	34.2	227.6	5/8	1	1-5/16	1-7/8	2-3/8
15	0.43	22	25.4	307.0	13/16	1-1/8	1-7/16	2	2-9/16
12	0.44	18	26.0	300.0	13/16	1-1/8	1-7/16	2	2-9/16
9	0.33	14	19.5	400.0	15/16	1-1/4	1-9/16	2-1/8	2-11/16
W5 x 19	0.64	W130 x 28	37.8	206.3	5/8	1	1-5/16	1-7/8	2-3/8
16	0.55	24	32.5	240.0	13/16	1-1/8	1-7/16	2	2-9/16
W4 x 13	0.55	W100 x 19	32.5	240.0	13/16	1-1/8	1-7/16	2	2-9/16

Note: Increased thickness may be applied when thickness applied to lower flange tips is reduced by one-half.