

**X650
Structural Steel Pipe Columns
CAFCO SprayFilm WB 3 and WB 4**

Standard Weight Pipe Columns

Nominal Dia.	Wall Thk	A/P	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour
4	0.237	0.22	102 x 6.0	45.0	173.0	NR	NR	NR
5	0.258	0.25	141 x 6.6	49.4	157.8	NR	NR	NR
6	0.28	0.27	168 x 7.1	53.8	144.8	NR	NR	NR
8	0.322	0.31	219 x 8.2	59.0	132.0	0.117	NR	NR
10	0.365	0.35	273 x 9.3	70.7	110.1	0.117	NR	NR
12	0.375	0.36	324 x 9.5	73.0	106.7	0.117	NR	NR

Extra Strong Pipe Columns

Nominal Dia.	Wall Thk	A/P	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour
4	0.337	0.31	102 x 8.6	62.0	125.6	0.117	NR	NR
5	0.375	0.35	141 x 9.5	70.2	111.0	0.117	NR	NR
6	0.432	0.40	168 x 11	81.0	96.2	0.117	NR	NR
8	0.5	0.47	219 x 12.7	94.5	82.4	0.097	0.138	0.202
10	0.5	0.48	273 x 12.7	95.6	81.4	0.097	0.138	0.202
12	0.5	0.48	324 x 12.7	96.4	80.8	0.097	0.138	0.202

Double Extra Strong Pipe Columns

Nominal Dia.	Wall Thk	A/P	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour
4	0.674	0.57	102 x 17.1	114.0	68.3	0.097	0.138	0.202
5	0.75	0.65	141 x 19.1	130.3	59.8	0.097	0.138	0.202
6	0.864	0.75	168 x 21.9	150.7	51.7	0.097	0.097	0.202
8	0.875	0.79	219 x 22.2	157.7	49.4	0.097	0.097	0.120

Note: A/P Ratio based on Design Formula. All thicknesses are expressed in inches.
To convert to Mills, multiply by 1000. To convert to mm, multiply by 25.4